

Aglime of Australia

PO Box 212, Belmont, WA 6984 Tel: (08) 9277 5529 Fax: (08) 9277 5379

Loading: Kim Riley 0408 092 022



GENERAL INFORMATION						
Pit Name	Aglime of Australia	Date of Analysis	January 19th 2015			
Location	Lancelin	Laboratory No.	B1501-0007-00012			
Product Description	Limesand	Product Screened	No			
Weigh System	Loadrite Loader Scales	Screen Size (mm)	N/A			

CODE OF PRACTICE APPROVED LABORATORY REPORT						
	THIS SAMPLE	RANGE FOR PIT	THIS SAMPLE	RANGE FOR PIT		
Sieve Range (mm)	% Weight		% Neutralising Value			
0.000 - 0.125	3.4	1.7 - 5.0	87.7	87.7 - 92.0		
0.125 - 0.250	51.4	35.5 - 60.4	89.5	87.5 - 92.9		
0.250 - 0.500	42.1	31.5 - 56.5	92.6	92.6 - 96.2		
0.500 – 1.000	3.0	1.9 - 9.7	95.5	66.4 - 95.5		
> 1.000	0.0	0.0 - 0.3	Insufficient Sample	Insufficient Sample		
Weighted Average NV			90.9	87.6 - 93.0		
Bulk NV	91.0	87.8 - 92.2	Proud to be independently audited by the Department of Agriculture and Food Western Australia.			
Calcium (Ca) (1 M HCI)	33.8	32.6 - 34.1				
Magnesium (Mg) (1 M HCI)	1.9	1.6 - 1.9				
Sodium (Na) (1 M HCI)	0.3	0.1 - 0.3				

Statement by Supplier: The above analysis, provided by a Code of Practice approved laboratory, is a true representation of the product being supplied from the nominated pit. Pit ranges have been calculated from the last 6 samples analysed.

Date: .22/1/2015 Name: Steve Carr (General Manager).

Disclaimer: Lime WA Inc. requires members to provide the above details in accordance with the industry Code of Practice requirements but makes no claims and provides no guarantees on the quality or suitability of the product supplied. Product supplied by Lime WA Inc. members occurs naturally and has a moisture retention capacity that varies according to seasonal conditions. As this cannot be controlled by suppliers, moisture level analyses are not included on this information sheet. Lime WA Inc. is not responsible for any claims and/or liabilities arising from the supply and/or use of the product supplied. However, users are invited to contact the Association on 0419 575 737 in the event of any dissatisfaction with the product description provided by accredited lime suppliers.